

Tubeless

Tire size Tire Designation	The Load Limits (lbs.) at Various Cold Inflation Pressures (psi) (The pressure is minimum for the load)											
		80	85	90	95	100	105	110	115	120	125	130
8R19.5	A	10440	11020	11460	11900	12340	12780	13220				
	D	5220	5510	5730	5950	6170	6390	6610				
	S	2835	2955	3075	3195	3305	3415	3525				
215/75R17.5	A	12792	13400	14000	14592	15192	15780	16380	16980	17572	18160	
	D	6396	6700	7000	7296	7596	7890	8190	8490	8786	9080	
	S	3375	3540	3695	3860	4010	4180	4330	4495	4650	4805	
235/75R17.5	A	15880	16680	17460	18220	18980	19740	20500	21240	21980	22700	
	D	7940	8340	8730	9110	9490	9870	10250	10620	10990	11350	
	S	4200	4410	4615	4820	5025	5225	5420	5620	5810	6005	
245/70R17.5	A	15880	16680	17460	18220	18980	19740	20500	21240	21980	22700	
	D	7940	8340	8730	9110	9490	9870	10250	10620	10990	11350	
	S	4200	4410	4615	4820	5025	5225	5420	5620	5810	6005	
10R22.5	A	16920	17640	18340	19040	19760	20300	20840	21420			
	D	8460	8820	9170	9520	9880	10150	10420	10710			
	S	4480	4675	4850	5025	5205	5360	5515	5675			
11R22.5	A	19040	19800	20820	21660	22500	23360	23580	23800	24020		
	D	9520	9900	10410	10830	11250	11680	11790	11900	12010		
	S	4990	5220	5510	5730	5950	6175	6320	6465	6610		
11R24.5	A	20280	21040	22040	22700	23360	24020	24820	25620	26440		
	D	10140	10520	11020	11350	11680	12010	12410	12810	13220		
	S	5310	5550	5840	6095	6350	6610	6790	6970	7160		
12R22.5	A	20760	21560	22700	23140	23580	24020	25060	26100	27120		
	D	10380	10780	11350	11570	11790	12010	12530	13050	13560		
	S	5450	5690	6005	6205	6405	6610	6870	7130	7390		
225/70R19.5	A	12000	12460	12980	13660	13960	14460	15000				
	D	6000	6230	6490	6830	6980	7230	7500				
	S	3195	3315	3450	3640	3715	3845	3970				
245/70R19.5	A	13660	14060	14620	15440	15760	16300	17200	17380	18160		
	D	6830	7030	7310	7720	7880	8150	8600	8690	9080		
	S	3640	3740	3890	4080	4190	4335	4540	4620	4805		
265/70R19.5	A	15000	15720	16380	17200	17620	17660	18700				
	D	7500	7860	8190	8600	8810	8830	9350				
	S	3970	4180	4355	4540	4685	4850	5070				
285/70R19.5	A				19400	20280	21160	21740	22220	26300		
	D				9700	10140	10580	10870	11110	13150		
	S				5160	5395	5635	5785	5980	6175		
245/75R22.5	A	14560	14460	15060	15880	16220						
	D	7280	7230	7530	7940	8110						
	S	3860	3975	4140	4300	4455	4610	4675				
265/75R22.5	A	15440	16160	16820	17640	18100	18740	19220				
	D	7720	8080	8410	8820	9050	9370	9610				
	S	4300	4440	4620	4805	4975	5150	5205				
255/70R22.5	A	15880	16440	17100	17640	17820	18440	18700	19660	20280		
	D	7940	8220	8550	8820	8910	9220	9350	9830	10140		
	S	4190	4370	4550	4675	4895	5065	5205	5400	5510		
275/70R22.5 16PR	A	16760	17640	18740	19620	20460	21600	22440	23580	24420	25580	
	D	8380	8820	9370	9810	10230	10800	11220	11790	12210	12790	
	S	4550	4785	5095	5325	5555	5865	6095	6405	6635	6940	
295/75R22.5	A	18160	18760	19540	20280	21040	21760	22700	23180	24020		
	D	9080	9380	9770	10140	10520	10880	11350	11590	12010		
	S	4940	5155	5370	5510	5780	5980	6175	6370	6610		
315/80R22.5* 20PR	A	22140	23000	23840	24660	25480	26280	27080	27860	28640	32100	32900
	D	11070	11500	11920	12330	12740	13140	13540	13930	14320	16050	16450
	S	6225	6495	6760	7020	7280	7530	7780	8025	8270	8275	9000
315/80R22.5* 22PR	A		24560	25440	26580	27420	28260	29320	30160	31220	31740	33020
	D		12280	12720	13290	13710	14130	14660	15080	15610	15870	16510
	S		7450	7705	8045	8300	8555	8885	9125	9445	9610	10000
285/75R24.5	A	18160	18960	19720	20820	21240	21980	22700	23440	24700		
	D	9080	9480	9860	10410	10620	10990	11350	11720	12350		
	S	4940	5210	5420	5675	5835	6040	6175	6440	6780		